
3ES-COMBI-FPK35

Exposure/Washout/Dryer



3ES-COMBI-FPK35

All-in one system, Exposure, Washout and Dryer up to a format size of 350 x 500 mm.

- LCD Control Panel, easily customize and setup for 9 different programs

Washout

- Equipped with flat brush, rotating plate board and temperature control between 15°C to 65°C (±2°C)
- Excellent permanent self-adhesive sticky plate board for foil based plates and Magnetic plate board for metal based plates
- Plate thickness adjustment.

Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation
- End of job alert

Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution for excellent drying and plate dimensional stability
- Programmable drying temperature between 15°C to 65°C (±2°C)
- End of job alert

*Optional










3ES-COMBI-FPK35

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-COMBI-FPK35
Maximum Plate Size	350 x 500 mm
Plate Type	Letterpress Plate / Water-wash
Washout Tank Capacity	46 liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40% -60%
Nominal Power	4.0kW
Nominal Current	6A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	190 kg net / 225 kg gross
Dimension (W*L*H)	820*830*1180 mm
Crate Dimension (approx.)	840*850*1430 mm



For all other information's or request please contact Mega.....

Mega Elektromekanik Mak. Iml. Ith. Ihr. San. Tic. Ltd. Sti.
Dudullu OSB DES-113 Sk. C-13 Blok N:58 34776 Umraniye Istanbul Turkey
T. +90 216 612 48 97 - 98 F. +90 216 612 15 72 info@3esmega.com








3ES-COMBI-FPK50

Exposure/Washout/Dryer



3ES-COMBI-FPK50

All-in one system, Exposure, Washout and Dryer up to a format size of 500 x 700 mm.

- LCD Control Panel, easily customize and setup for 9 different programs

Washout

- Equipped with flat brush, rotating plate board and temperature control between 15°C to 65°C (±2°C)
- Excellent permanent self-adhesive sticky plate board for foil based plates and Magnetic plate board for metal based plates
- Plate thickness adjustment

Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation
- End of job alert

Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution for excellent drying and plate dimensional stability
- Programmable drying temperature between 15°C to 65°C (±2°C)










3ES-COMBI-FPK50

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-COMBI-FPK50
Maximum Plate Size	500 x 700 mm
Plate Type	Letterpress plate / Water-wash
Washout Tank Capacity	64 liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40% -60%
Fresh Water Connection	R3/4"
Washing Solution Outlet	Ø20 mm
Overflow Outlet	Ø20 mm
Compressed Air	6 bar minimum - 2001/min (For automatic lid opening-closing option)
Nominal Power	6.0kW
Nominal Current	10A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	275 kg net / 310 kg gross
Dimension (WxLxH)	1120*1020*1180 mm
Crate Dimension (approx.)	1220*1120*1430 mm



For all other information's or request please contact Mega.....






www.3esmega.com





3ES-COMBI-FPK50s

Exposure/Washout/Dryer



3ES-COMBI-FPK50s

All-in one system, Exposure, Washout and Dryer up to a format size of 500 x 700 mm.

- Stainless steel body, 7" Touch screen panel, easily customize and setup for 9 different programs
- End of job alert

Washout

- Equipped with flat brush, rotating plate board and temperature control between 15°C to 65°C (±2°C)
- Excellent permanent self-adhesive sticky plate board for foil based plates and Magnetic plate board for metal based plates
- Automatic plate thickness adjustment
- Automatic lid opening/closing

Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation

Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution for excellent drying and plate dimensional stability
- Programmable drying temperature between 15°C to 65°C (±2°C)










3ES-COMBI-FPK50s

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-COMBI-FPK50s
Maximum Plate Size	500 x 700 mm
Plate Type	Letterpress plate / Water-wash
Washout Tank Capacity	64 liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40% -60%
Fresh Water Connection	R3/4"
Washing Solution Outlet	Ø20 mm
Overflow Outlet	Ø20 mm
Compressed Air	6 bar minimum - 2001/min (For automatic lid opening-closing option)
Nominal Power	6.0kW
Nominal Current	10A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	275 kg net / 310 kg gross
Dimension (WxLxH)	1120*1020*1180 mm
Crate Dimension (approx.)	1220*1120*1430 mm



For all other information's or request please contact Mega.....








3ES-COMBI-FPK35130f

Exposure/Washout/Dryer



3ES-COMBI-FPK35130f

All-in one system, Exposure, Washout and Dryer up to a format size of 350 x 1300 mm.

- Stainless steel body
- 7" Touch screen and easily customize and setup for 9 different programs
- End of job alert

Washout

- Equipped with flat brush, rotating plate board, automatic lid opening/closing and temperature control between 15°C to 65°C (±2°C)
- Includes permanent self-adhesive sticky plate board for foil based plates or magnetic plate board for metal based plates
- Automatic plate thickness adjustment
- Automatic lid opening/closing

Exposure

- UVA exposing lamps
- Powerful and fast vacuum system and vacuum indicator on control panel
- Defective lamp indicator
- Lamp temperature control and regulation

Drying

- Two drying drawer
- Timer for each drawer
- Uniform temperature distribution
- Programmable drying temperature between 15°C to 65°C (±2°C)










3ES-COMBI-FPK35130f

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-COMBI-FPK35130f
Maximum Plate Size	350 x 1300 mm
Plate Type	Analog & Digital/ Letterpress / Water-wash
Washout Tank Capacity	71liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40%-60%
Compressed Air	male coupling 8 mm/6 bar minimum - 200l/min
Nominal Power	6.0kW
Nominal Current	10A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	275 kg net / 310 kg gross
Dimension	1840*1270*1180 mm
Crate Dimension (approx.)	1220*1120*1430 mm



For all other information's or request please contact Mega.....

Mega Elektromekanik Mak. Iml. Ith. Ihr. San. Tic. Ltd. Sti.
Dudullu OSB DES-113 Sk. C-13 Blok N:58 34776 Umraniye Istanbul Turkey
T. +90 216 612 48 97 - 98 F. +90 216 612 15 72 info@3esmega.com

www.3esmega.com








3ES-FPK50s

Washout





3ES-FPK50s

Photopolymer printing plate washout up to a format size of 500×700 mm.

- Stainless steel body, 7" Touch screen easily customize and setup for different programs
- Equipped with flat brush, rotating plate board, automatic lid opening/closing and temperature control between 15°C to 65°C (±2°C)
- Includes permanent self-adhesive sticky plate board for foil based plates or magnetic plate board for metal based plates
- Automatic plate thickness adjustment
- End of job alert.








3ES-FPK50s

Exposure/Washout/Dryer



Technical Data

Product Name	3ES-FPK50s
Maximum Plate Size	500 x 700 mm
Plate Type	Letterpress / Water-wash
Washout Tank Capacity	71liters
Environmental Requirements	Temperature: 15°C to 30°C Humidity: 40%-60%
Compressed Air	Male coupling 8 mm/6 bar minimum
Nominal Power	3.0kW
Nominal Current	6A 400 V AC (3 Ph/N/PE)50/60 Hz
Weight	135 kg net / 195 kg gross
Dimension	1250*1100*1180 mm
Crate Dimension (approx.)	1350*1200*1430 mm



For all other information's or request please contact Mega.....





www.3esmega.com

